

Dichroic lightfixtures/ Foco dicroico

Small compact spotlights designed to illuminate no more than 3 metres high water jets, without a large diameter opening and ideal for secondary effects in ornamental fountains. Their cable glands designed and manufactured by Safe-Rain ensure an IP68 degree of protection. They can house 50mm MR16 dichroic lamps or similar. LED lamps available in 3000K white, 6000K white and RGB models.

Focos compactos de pequeño tamaño destinados a la iluminación de chorros no superiores a 3 metros de altura, sin gran apertura en diámetro e ideales para efectos secundarios en fuentes ornamentales. Sus prensaestopas diseñados y fabricados por Safe-Rain aseguran un grado de protección IP68. Pueden alojar en su interior lámparas de tipo MR16 dicroicas de 50mm o similar. Disponibles lámparas LED modelos blanco 3000K, blanco 6000K y RGB.



Certifications/ Certificaciones

IP68



ON STOCK


LED

RGB


PLC + HMI



Polyamide



Brass



Light charts/ Gráficos de iluminación.

Color	White /Blanco 6000k		White /Blanco 3000k		RGB		
Distance/ Distancia	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	Beam/ Haz de luz (m)	Centre/ Centro	
1,0 m	Ø 0,72	1754 lx	Ø 0,68	970 lx	Ø0,55	1062 lx	
1,5 m	Ø 1,10	584 lx	Ø 1,03	431 lx	Ø0,82	472 lx	
2,0 m	Ø 1,44	438 lx	Ø 1,37	243 lx	Ø1,10	265 lx	
2,5m	Ø2,16	281lx					

Details/ Detalles				Electrical data/ Datos eléctricos						
Polyamide 6-6/ Po- liamida 6-6		Brass/ Latón		Lamp/ Lámpara						
Reference/ Referencia	Weight/ Peso	Reference/ Referencia	Weight/ Peso	Color/ Color	Beam angle/ Ángulo	Lumens/ Lúmenes	Power/ Potencia	Voltage/ Voltaje	Lamp Ref./ Ref. Lámpara	Electrical connec- tion/ Conexión eléc- trica
F5450218	0,36 Kg	F5460219	0,94 Kg	White/ Blanco 6000K	45°	500 Lm	4W	12V AC	F5642054	1PG16 Ø6/9/12
F5457418	0,36 Kg	F5467419	0,94 Kg	White/ Blanco 3000K	38°	480 Lm	6W	12V AC	F5642043	
F5455214	0,46 Kg	F5465215	1,05 Kg	RGB	25°	165 Lm	5,5W	12 / 24V DC	F5642537	0,5m H05RN-F 4x0,75mm²
F5430014	0,32 Kg	F5440015	0,91 Kg	Without lamp/ Sin lámpara						1PG16 Ø6/9/12